

Strain Relief Grip, Deluxe Cord, NPT 3", Straight Male, Cable Range 1.937-2.062"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL&CSA, CE certified



Classification	
Material Code	6003489
Part Number	-
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 3", straight male, cable range 1.937-2.062"
Details	
Cable Range	1.937-2.062 in 49.20 -52.37 mm
Thread Size	NPT 3"
Mesh Length	16.0 in 406.4 mm
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package	
Packaging Quantity	1 pcs
Weight, gross	2.282 lb 1.035 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant

For more information, please visit: www.maxdao.com

 \bowtie

in

©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 27, 2023 Public Page 1 of 2

DATASHEET

CE

Compliant



Page 2 of 2

For more information, please visit: www.maxdao.com

in

©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 27, 2023 Public

 \square