## ΜΑΧΡΔΟ

## Strain Relief Grip, Deluxe Cord, NPT 3", Straight Male, Cable Range 2.437-2.625"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- **UL&CSA**, CE certified



Classification	
Material Code	6003600
Part Number	-
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 3", straight male, cable range 2.437-2.625"
Details	
Cable Range	2.437-2.625 in   61.90 -66.68 mm
Thread Size	NPT 3"
Mesh Length	18.0 in   457.2 mm
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package	
Packaging Quantity	1 pcs
Weight, gross	2.707 lb   1.228 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant

For more information, please visit: www.maxdao.com





CE Compliant

