

## Strain Relief Grip, Deluxe Cord, NPT1/2", Straight Female, Cable Range 0.500-0.625"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- CE certified



### Classification

|                    |  |
|--------------------|--|
| Material Code      | 6003593  |
| Part Number        | -  |
| Status             | Active   |
| Detail Description | Strain relief grip, deluxe cord, NPT 1/2", straight female, cable range 0.500-0.625" |

### Details

|               |                                 |
|---------------|---------------------------------|
| Cable Range   | 0.500-0.625 in   12.70-15.88 mm |
| Thread Size   | NPT 1/2"                        |
| Mesh Length   | 6.5 in   165.1 mm               |
| Mesh Material | Stainless Steel                 |
| Body Material | Aluminum                        |

### Performance

|                        |  |
|------------------------|--|
| Flammability           | UL 94HB & UL 94V-2   |
| Hazardous Locations    | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F)  |
| Wet Locations          | Suitable for use in wet locations when used with a listed sealing ring between box and fitting               |

### Package

|                    |                     |
|--------------------|---------------------|
| Packaging Quantity | 1 pcs               |
| Weight, gross      | 0.104 lb   0.047 kg |

### Certifications

|               |  |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS          | Compliant  |
| CE            | Compliant  |