

Strain Relief Grip, Dust Tight, NPT 1/2", Insulated, Cable Range 0.30-0.43"

- For indoor use in wiring of enclosures, power boxes, machine tools, power centers and bus drop systems
- Prevents severe cable bending and pull-out
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Easy installation
- UL&CSA, CE certified



Classification

| | |
|--------------------|--|
| Material Number | 6003046 |
| Part Number | - |
| Status | Active |
| Detail Description | Strain relief grip, dust tight, NPT 1/2", cable range 0.30-0.43", with lock nut and Insulating bushing |

Details

| | |
|------------------------|-------------------------------|
| Cable Range | 0.30-0.43 in 7.62 -10.92 mm |
| Thread Size | NPT 1/2" |
| Mesh Length | 4.5 in 114.3 mm |
| Approx. Break Strength | 300 lbs 136.1 kg |
| Mesh Material | Galvanized Steel |
| Body Material | Aluminum |

Performance

| | |
|---------------------|--|
| Flammability | UL 94HB & UL 94V-2 |
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |

Package

| | |
|--------------------|---------------------|
| Packaging Quantity | 1 kit |
| Weight, gross | 0.062 lb 0.028 kg |

Certifications

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| UL&CSA | Compliant |
| CE | Compliant |