

Strain Relief Grip, Dust Tight, NPT 3/4", Insulated, Stainless Steel ,Cable Range 0.52-0.73"

- For indoor and outdoor use in wiring of enclosures, power boxes, machine tools, power centers and bus drop systems
- Prevents severe cable bending and pull-out
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Easy installation
- UL&CSA, CE certified



Classification

| | |
|--------------------|---|
| Material Number | 6004423 |
| Part Number | - |
| Status | Active |
| Detail Description | Strain relief grip, dust tight, NPT 3/4", Stainless Steel, cable range 0.52-0.73", with lock nut and Insulating bushing |

Details

| | |
|------------------------|--------------------------------|
| Cable Range | 0.52-0.73 in 13.21 -18.54 mm |
| Thread Size | NPT 3/4" |
| Mesh Length | 6.5 in 165.1 mm |
| Approx. Break Strength | 450 lbs 204.1 kg |
| Mesh Material | Stainless Steel |
| Body Material | Aluminum |

Performance

| | |
|---------------------|--|
| Flammability | UL 94HB & UL 94V-2 |
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |

Package

| | |
|--------------------|---------------------|
| Packaging Quantity | 1 kit |
| Weight, gross | 0.119 lb 0.054 kg |

Certifications

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| UL&CSA | Compliant |
| CE | Compliant |

