

Strain Relief Grip, Dust Tight, NPT 3/4", Non-Insulated, Cable Range 0.52-0.73"

- For indoor use in wiring of enclosures, power boxes, machine tools, power centers and bus drop systems
- Prevents severe cable bending and pull-out
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Easy installation
- UL&CSA, CE certified

**Classification**

Material Number	6003063
Part Number	-
Status	Active
Detail Description	Strain relief grip, dust tight, NPT 3/4", cable range 0.52-0.73", with lock nut

Details

Cable Range	0.52-0.73 in 13.21 -18.54 mm
Thread Size	NPT 3/4"
Mesh Length	6.5 in 165.1 mm
Approx. Break Strength	450 lbs 204.1 kg
Mesh Material	Galvanized Steel
Body Material	Aluminum

Performance

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2

Package

Packaging Quantity	1 kit
Weight, gross	0.117 lb 0.053 kg

Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant
CE	Compliant