

Feeder Cable Clamp,for 12×(4-7)+6×(18-19)mm Cable

- Easy and quick installation ۲
- Robust design & material for outdoor use
- Operation Temperature -40~85 ℃ •
- Suitable for cable type (4-7)+(18-19)mm •



| Product Classification | |
|---------------------------------|---|
| Material Code | 6006289 |
| Part Number | - |
| Status | Active |
| Detail Description | Feeder cable clamp,for 12×(4-7)+6×(18-19)mm cable,18 way includes hardware and angle adapter |
| General Specifications | |
| Material Parts | Stainless steel + PP+EPDM |
| Mounting | M8 hardware |
| Cables per hanger | 18 |
| Color | Black |
| Dimensions | |
| Height | 40 mm 1.57 in |
| Width | 64 mm 2.52 in |
| Length | 295 mm 11.61 in |
| Compatible cable OD, maximum | 18-19 mm 0.71-0.75 in |
| Compatible cable OD, minimum | 4-7 mm 0.16-0.28 in |
| Environmental Specifications | |
| Salt spray test for metal parts | ≥48 Hours,base on ISO 9227: 2017 |
| Operating temperature | -40°C ~ 85°C |
| Packaging and Weights | |
| Height, packed | 205 mm 8.1 in |
| Width, packed | 325 mm 12.8 in |
| Length, packed | 495 mm 19.4 in |
| UOM | Pcs |
| | |

For more information, please visit: www.maxdao.com

 \sim

in

[©]Copyright 2023 Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Released: Apr 10, 2023 Public

DATASHEET



| Packaging | Bag |
|-------------------------------|---|
| Weight, gross | 0.38 kg 0.84 lb |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed,manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| | |

For more information, please visit: www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Released: Apr 10, 2023 Public