
## ΜΑΧΡΔΟ

## Feeder Cable Clamp, for 2×(4.5-7)+2×(10-15)mm Cable

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 ℃
- Suitable for cable type (4.5-7)+(10-15)mm



	lassific	

**Material Code** 6004559

Part Number

Status Active

Feeder cable clamp, for 2×(4.5-7)+2×(10-15)mm cable, 4 way, **Detail Description** includes hardware and angle adapter,include MAXDAO logo

**General Specifications** 

**Material Parts** Q235 plated dacrol+PP+EPDM

Mounting M6 hardware

4 Cables per hanger

Color Black

**Dimensions** 

Height 36 mm | 1.42 in

Width 40 mm | 1.57 in

165 mm | 6.50 in Length

10-15 mm | 0.39-0.59 in Compatible cable OD, maximum

Compatible cable OD, minimum 4.5-7 mm | 0.18-0.28 in

**Environmental Specifications** 

Salt spray test for metal parts ≥120 Hours,base on ISO 9227: 2017

-40°C ~ 85°C Operating temperature

**Packaging and Weights** 

Height, packed 205 mm | 8.1 in

Width, packed 325 mm | 12.8 in

Length, packed 495 mm | 19.4 in

Packaging Quantity and UOM 1 pcs

For more information, please visit: www.maxdao.com





Weight, gross 0.19 kg | 0.42 lb

**Certifications and Compliance** 

ISO 9001:2015

RoHS

Designed, manufactured and/or distributed under this

quality management system

Compliant



For more information, please visit: www.maxdao.com