
## ΜΑΧΡΔΟ

## Feeder Cable Clamp, for $3\times(4-7)+3\times(9-14)$ mm Cable

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 ℃
- Suitable for cable type (4-7)+(9-14)mm



ı	D	r	٠,	d	<u>_</u>	t i	^	la	92	if	ic	۔	+i	^	n

Material Code 6004345

Part Number

Status Active

Feeder cable clamp, for  $3 \times (4-7)+3 \times (9-14)$ mm cable, 6 way, **Detail Description** 

includes hardware and angle adapter, include metal gasket

**General Specifications** 

**Material Parts** Stainless steel+PP+EPDM

Mounting M8 hardware

Cables per hanger 6

Color Black

**Dimensions** 

Height 40 mm | 1.57 in

Width 44 mm | 1.73 in

185 mm | 7.28 in Length

9-14 mm | 0.35-0.55 in Compatible cable OD, maximum

Compatible cable OD, minimum 4-7 mm | 0.16-0.28 in

**Environmental Specifications** 

Salt spray test for metal parts ≥48 Hours,base on ISO 9227: 2017

-40°C ~ 85°C Operating temperature

**Packaging and Weights** 

Height, packed 205 mm | 8.1 in

Width, packed 325 mm | 12.8 in

Length, packed 495 mm | 19.4 in

Packaging Quantity and UOM 1 pcs



Page 1 of 2

TEMPLATE#ITM-04-01, Version:A/3, DATE:03/04/2023



Weight, gross 0.26 kg | 0.58 lb

**Certifications and Compliance** 

ISO 9001:2015

RoHS

Designed,manufactured and/or distributed under this

quality management system

Compliant



For more information, please visit: www.maxdao.com