ΜΑΧΡΔΟ

Feeder Cable Clamp, for $6\times(4-7)+4\times(9-11)$ mm Cable

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 ℃
- Suitable for cable type (4-7)+(9-11)mm



P	rod	luct Cl	lassifica [.]	tion

Material Code 6004696

Part Number

Status Active

Feeder cable clamp, for 6×(4-7)+4×(9-11)mm cable, 10 way, **Detail Description**

includes hardware and angle adapter

General Specifications

Material Parts Stainless steel+PP+EPDM

Mounting M8 hardware

Cables per hanger 10

Color Black

Dimensions

Height 40 mm | 1.57 in

Width 39 mm | 1.54 in

225 mm | 8.86 in Length

9-11 mm | 0.35-0.43 in Compatible cable OD, maximum

Compatible cable OD, minimum 4-7 mm | 0.16-0.28 in

Environmental Specifications

Salt spray test for metal parts ≥48 Hours,base on ISO 9227: 2017

Operating temperature -40°C ~ 85°C

Packaging and Weights

Height, packed 205 mm | 8.1 in

Width, packed 325 mm | 12.8 in

Length, packed 495 mm | 19.4 in

Packaging Quantity and UOM 1 pcs

For more information, please visit: www.maxdao.com





Weight, gross 0.25 kg | 0.55 lb

Certifications and Compliance

ISO 9001:2015

RoHS

Designed, manufactured and/or distributed under this

quality management system

Compliant



For more information, please visit: www.maxdao.com