# ΜΑΧΟΔο

# Feeder Cable Clamp, for 6×(4-7)+6×(9-14) mm Cable

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 ℃
- Suitable for cable type (4-7)+(9-14) mm



Droc	luct	Cla	ccifi	catio	n
Pr ()(		l la	•	l allo	

Material Code 6002144

Part Number

Status Active

Feeder cable clamp, for 6×(4-7)+6×(9-14)mm cable, 12 way, **Detail Description** 

includes hardware and angle adapter

#### **General Specifications**

**Material Parts** Stainless steel+PP+EPDM

Mounting M8 hardware

Cables per hanger 12

Black Color

#### **Dimensions**

Height 40 mm | 1.57 in

Width 44 mm | 1.73 in

Length 245 mm | 9.65 in

9-14 mm | 0.35-0.55 in Compatible cable OD, maximum

Compatible cable OD, minimum 4-7 mm | 0.16-0.28 in

## **Environmental Specifications**

Salt spray test for metal parts ≥48 Hours,base on ISO 9227: 2017

-40°C ~ 85°C Operating temperature

## **Packaging and Weights**

Height, packed 205 mm | 8.1 in Width, packed 325 mm | 12.8 in

Length, packed 495 mm | 19.4 in

Packaging Quantity and UOM 1 pcs

For more information, please visit: www.maxdao.com





Weight, gross 0.32 kg | 0.71 lb

**Certifications and Compliance** 

ISO 9001:2015

RoHS

Designed, manufactured and/or distributed under this

quality management system

Compliant



For more information, please visit: www.maxdao.com