

GST Grounding Kit ,for cable 3/8" ,1.5m

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Suitable for screen diameter of cable OD 3/8"
- Operation Temperature -40~70 °C
- Waterproof IP68



Product Classification

Material Number	6005587
Status	Active
Detail Description	GST Grounding Kit,for cable3/8 " ,1.5m,installation accessories including

General Specifications

Bonding Conductor Material	Copper
Bonding Conductor Wire Size	16mm ²
Grounding Strap Material	Copper, Tin Plated
Lug Type	Two-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel

Dimensions

Bonding Conductor Length	1.5m 59.1 in
Lug Hole Size	3/8"
Screw Size	3/8"x1"

Electrical Specifications

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

Packaging and Weights

Height, packed	180 mm 7.0 in
Width, packed	310 mm 12.2 in
Length, packed	400 mm 15.75 in
Included	Grounding kit 3/8"x1" screw 3/8" spring washer 3/8" flat washer 3/8" nut

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 23, 2023
 Public

Page 1 of 2

UOM	1 Kit
Packaging	Bag
Weight, gross	0.526 kg 1.159 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

