


GST Grounding Kit ,for cable 8.9mm,1.0m

- Easy and quick installation
- Low contact transition resistance of maximum $10m\Omega$
- Suitable for screen diameter of cable OD 8.9mm
- Operation Temperature -40~70 $^{\circ}\mathrm{C}$
- **Waterproof IP68**



Product Classification	
Material Number	6005473
Status	Active
Detail Description	GST Grounding Kit,for cable 8.9mm,1.0m,installation accessories including
General Specifications	
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG6
Grounding Strap Material	Copper,Tin Plated
Lug Type	Two-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
Dimensions	
Bonding Conductor Length	1.0m 39.3 in
Lug Hole Size	M8
Screw Size	M8x25
Electrical Specifications	
Contact Transition Resistance	Maximum 10mΩ
Packaging and Weights	
Height, packed	180 mm 7.0 in
Width, packed	310 mm 12.2 in
Length, packed	400 mm 15.75 in
Included	Grounding kit M8x25 screw M8 spring washer M8 fla washer M8 nut



www.maxdao.com









UOM 1 Kit

Packaging Bag

0.316 kg | 0.696 lb Weight, gross

Certifications and Compliance

Designed, manufactured and/or distributed under this ISO 9001:2015

quality management system

ROHS Compliant



