

## Gasket O-ring 2.62×61.6mm

- Quick and easy to install
- Excellent seal performance
- Suitable for various application environment



### Product Classification

Material Number	6004130
Part Number	-
Status	Active
Detail description	Gasket O-ring 2.62×61.6mm

### General Specifications

Material	Butyl rubber
Color	Black

### Dimensions

Rubber diameter	2.62 mm   0.1 in
Inner hole diameter	61.6 mm   2.43 in

### Mechanical Specifications

Specific gravity, g/cm <sup>3</sup>	2.05±0.1, based on GB/T531-1999
Hardness/shore A	70±10, based on GB/T533-1991
Tensile strength/MPa	>1.3, based on GB/T528-1998
Elongation at break/%	100-300, based on GB/T528-1998
Compression set, 70hrs@100°C, % max	<32, based on ASTM D395

### Electrical Specifications

Volume resistance, ohm-cm, max	<0.1, based on MIL-G-83528
Shielding effectiveness, dB, min	200kHz(H Field), result 80,, based on MIL-G-83528
	100MHz(H Field), result 100,, based on MIL-G-83528
	500MHz(H Field), result 100,, based on MIL-G-83528
	2GHz(Plane Wave), result 90,, based on MIL-G-83528
	10GHz(Plane Wave), result 85,, based on MIL-G-83528

### Environmental Specifications

For more information, please visit:  
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 8, 2023

Public

Operating temperature	-40°C to +125°C (-40°F to +257°F)
Low temperature flex TR10, °C, min	-55, based on MIL-G-83528
Maximum continuous use temperature, °C	150, based on MIL-G-83528
Heat aging, volume resistance, ohm-cm, max	0.12, based on MIL-G-83528

---

**Packaging and Weights**

---

Bag width	200 mm   7.87 in
Bag length	200 mm   7.87 in
Packaging quantity and UOM	1 pcs
Weight gross	0.00137 kg   0.003 lb

---

**Certifications and Compliance**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

