

Heat Shrink Tube,black,ID before shrink 0.375'' ,with UL certificated,48'' length

- UL certificated
- Good weatherproof performance
- Various range of application

**Product Classification**

Material Code	6007257
Part Number	-
Status	Active
Detail description	Heat shrink tube,black,ID before shrink 0.375'',with UL certificated,48''length

General Specifications

Material	Ethylene vinyl acetate copolymer(EVA)
Applied pole size	φ4.7-8.0mm
Color	Black
Glued(Y/N)	N

Dimensions

Inner diameter(ID) before shrink	9 mm 0.375 in
Thickness before shrink	0.3 mm 0.012 in
Inner diameter(ID) after shrink	≤4.5 mm ≤0.015 in
Thickness after shrink	0.56 mm 0.002 in
Shrink ratio	2:1

Environmental Specifications

Operating temperature	-55°C to +125°C (-67°F to +257°F)
Temperature starting shrink	+70°C (158°F)
Temperature totally shrink	+125°C (+257°F)

Packaging and Weights

Bag width	130 mm 5.12 in
Bag length	1370 mm 53.94 in

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised:Feb 25, 2023

Public

Length per pcs	1.22m 48 in
Packaging quantity and UOM	Bag of 100
Weight gross	1.43 kg 3.15 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UL	Compliant

