

Heat Shrink Tube,black,ID before shrink 0.5"

- Good weatherproof performance
- Various range of application



Product Classification

| | |
|--------------------|--|
| Material Code | 6006896 |
| Part Number | - |
| Status | Active |
| Detail description | Heat shrink tube,black,ID before shrink 0.5" |

General Specifications

| | |
|-------------------|---------------------------------------|
| Material | Ethylene vinyl acetate copolymer(EVA) |
| Applied pole size | φ6.2-11.0mm |
| Color | Black |
| Glued(Y/N) | N |

Dimensions

| | |
|----------------------------------|--------------------|
| Inner diameter(ID) before shrink | 12.5 mm 0.5 in |
| Thickness before shrink | 0.3 mm 0.012 in |
| Inner diameter(ID) after shrink | ≤6 mm ≤0.236 in |
| Thickness after shrink | 0.56 mm 0.002 in |
| Shrink ratio | 2:1 |

Environmental Specifications

| | |
|-----------------------------|-----------------------------------|
| Operating temperature | -55°C to +125°C (-67°F to +257°F) |
| Temperature starting shrink | +70°C (158°F) |
| Temperature totally shrink | +125°C (+257°F) |

Packaging and Weights

| | |
|----------------|------------------|
| Roll diameter | 500 mm 1.64 in |
| Roll height | 34 mm 0.11 in |
| Meter per roll | 100m |

| | |
|----------------------------|--------------------|
| Packaging quantity and UOM | 1 roll |
| Weight gross | 1.887 kg 4.16 lb |

Certifications and Compliance

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| ROHS | Compliant |

