

**Heat Shrink Tube,black,ID before shrink 0.5",with UL certificated**

- **UL certificated**
- **Good weatherproof performance**
- **Various range of application**

**Product Classification**

Material Code	6007249
Part Number	-
Status	Active
Detail description	Heat shrink tube,black,ID before shrink 0.5",with UL certificated

**General Specifications**

Material	Ethylene vinyl acetate copolymer(EVA)
Applied pole size	φ6.2-11.0mm
Color	Black
Glued(Y/N)	N

**Dimensions**

Inner diameter(ID) before shrink	12.5 mm   0.5 in
Thickness before shrink	0.3 mm   0.012 in
Inner diameter(ID) after shrink	≤6 mm   ≤0.236 in
Thickness after shrink	0.56 mm   0.002 in
Shrink ratio	2:1

**Environmental Specifications**

Operating temperature	-55°C to +125°C (-67°F to +257°F)
Temperature starting shrink	+70°C (158°F)
Temperature totally shrink	+125°C (+257°F)

**Packaging and Weights**

Roll diameter	500 mm   1.64 in
Roll height	34 mm   0.11 in
Meter per roll	30.5m

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised:Feb 24, 2023

Public

Packaging quantity and UOM	1 roll
Weight gross	0.72 kg   1.59 lb

---

**Certifications and Compliance**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UL	Compliant

