

Heat Shrink Tube,transparent,ID before shrink 0.25"

- Good weatherproof performance
- Various range of application



Product Classification	
Material Code	6006891
Part Number	-
Status	Active
Detail description	Heat shrink tube,transparent,ID before shrink 0.25'
General Specifications	
Material	Ethylene vinyl acetate copolymer(EVA)
Applied pole size	φ3.1-5.4mm
Color	Transparent
Glued(Y/N)	N
Dimensions	
Inner diameter(ID) before shrink	6.5 mm 0.26 in
Thickness before shrink	0.28 mm 0.011 in
Inner diameter(ID) after shrink	≤3 mm ≤0.12 in
Thickness after shrink	0.55 mm 0.022 in
Shrink ratio	2:1
Environmental Specifications	
Operating temperature	-55℃ to +125℃(-67℉ to +257℉)
Temperature starting shrink	+70℃(158°F)
Temperature totally shrink	+125℃(+257°F)
Packaging and Weights	
Roll diameter	500 mm 1.64 in
Roll height	34 mm 0.11 in
Meter per roll	100m

For more information, please visit: www.maxdao.com

(iii)



DOC#ITM04-01, Version:A/2, Updated:02/21/2023



Packaging quantity and UOM 1 roll

Weight gross 0.937 kg | 2.07 lb

Certifications and Compliance

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

Compliant

Compliant



www.maxdao.com

For more information, please visit: