

**Heat Shrink Tube,transparent,ID before shrink 0.25",with UL certificated**

- **UL certificated**
- **Good weatherproof performance**
- **Various range of application**

**Product Classification**

Material Number	6007252
Part Number	-
Status	Active
Detail description	Heat shrink tube,transparent,ID before shrink 0.25",with UL certificated

**General Specifications**

Material	Ethylene vinyl acetate copolymer(EVA)
Applied pole size	φ3.1-φ5.4mm
Color	Transparent
Glued(Y/N)	N

**Dimensions**

Inner diameter(ID) before shrink	6 mm   0.25 in
Thickness before shrink	0.28 mm   0.011 in
Inner diameter(ID) after shrink	≤3 mm   ≤0.12 in
Thickness after shrink	0.56 mm   0.022 in
Shrink ratio	2:1

**Environmental Specifications**

Operating temperature	-55°C to +125°C (-67°F to +257°F)
Temperature starting shrink	+70°C (158°F)
Temperature totally shrink	+125°C (+257°F)

**Packaging and Weights**

Roll diameter	500 mm   1.64 in
Roll height	34 mm   0.11 in
Meter per roll	30.5m

Packaging quantity and UOM 1 roll  
Weight gross 0.462 kg | 1.02 lb

---

**Certifications and Compliance**

---

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system  
ROHS Compliant  
UL Compliant

