

Heat Shrink Tube, transparent, ID before shrink 0.375''

- Good weatherproof performance
- Various range of application



Product Classification		
Material Code	6006892	
Part Number	-	
Status	Active	
Detail description	Heat shrink tube,transparent,ID before shrink 0.375'	
General Specifications		
Material	Ethylene vinyl acetate copolymer(EVA)	
Applied pole size	φ4.7-8.0mm	
Color	Transparent	
Glued(Y/N)	Ν	
Dimensions		
Inner diameter(ID) before shrink	9.5 mm 0.37 in	
Thickness before shrink	0.3 mm 0.012 in	
Inner diameter(ID) after shrink	≤4.5 mm ≤0.015 in	
Thickness after shrink	0.6 mm 0.023 in	
Shrink ratio	2:1	
Environmental Specifications		
Operating temperature	-55℃ to +125℃(-67°F to +257°F)	
Temperature starting shrink	+70℃(158°F)	
Temperature totally shrink	+125°C(+257°F)	
Packaging and Weights		
Roll diameter	500 mm 1.64 in	
Roll height	34 mm 0.11 in	
Meter per roll	100m	

 \boxtimes

(in

©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised:Feb 24, 2023 Public Page 1 of 2

DATASHEET



Packaging quantity and UOM	1 roll
Weight gross	1.26 kg 2.78 lb
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

For more information, please visit: www.maxdao.com



©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised:Feb 24, 2023 Public