

Heat Shrink Tube, transparent, ID before shrink 0.5"

- **Good weatherproof performance**
- Various range of application



Product Classification	
Material Code	6006893
Part Number	-
Status	Active
Detail description	Heat shrink tube,transparent,ID before shrink 0.5'
General Specifications	
Material	Ethylene vinyl acetate copolymer(EVA)
Applied pole size	φ6.2-11.0mm
Color	Transparent
Glued(Y/N)	N
Dimensions	
Inner diameter(ID) before shrink	12.5 mm 0.5 in
Thickness before shrink	0.3 mm 0.012 in
Inner diameter(ID) after shrink	≤6 mm ≤0.236 in
Thickness after shrink	0.6 mm 0.024 in
Shrink ratio	2:1
Environmental Specifications	
Operating temperature	-55℃ to +125℃(-67℉ to +257℉)
Temperature starting shrink	+70°C(158°F)
Temperature totally shrink	+125°C(+257°F)
Packaging and Weights	
Roll diameter	500 mm 1.64 in
Roll height	34 mm 0.11 in
Meter per roll	100m

For more information, please visit:

www.maxdao.com





DOC#ITM04-01, Version:A/2, Updated:02/21/2023



Packaging quantity and UOM 1 roll

Weight gross 1.524 kg | 3.36 lb

Certifications and Compliance

ISO 9001:2015

Designed, manufactured and/or distributed under this

quality management system

ROHS Compliant

For more information, please visit: