

Heat Shrink Tube,transparent,ID before shrink 0.5",with UL certificated

- UL certificated
- Good weatherproof performance
- Various range of application



Product Classification

Material Code	6007254
Part Number	-
Status	Active
Detail description	Heat shrink tube,transparent,ID before shrink 0.5",with UL certificated

General Specifications

Material	Ethylene vinyl acetate copolymer(EVA)
Applied pole size	φ6.2-11.0mm
Color	Transparent
Glued(Y/N)	N

Dimensions

Inner diameter(ID) before shrink	12.5 mm 0.5 in
Thickness before shrink	0.3 mm 0.012 in
Inner diameter(ID) after shrink	≤6 mm ≤0.236 in
Thickness after shrink	0.56 mm 0.002 in
Shrink ratio	2:1

Environmental Specifications

Operating temperature	-55°C to +125°C(-67°F to +257°F)
Temperature starting shrink	+70°C(158°F)
Temperature totally shrink	+125°C(+257°F)

Packaging and Weights

Roll diameter	500 mm 1.64 in
Roll height	34 mm 0.11 in
Meter per roll	30.5m

Packaging quantity and UOM 1 roll
Weight gross 0.629 kg | 1.39 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UL	Compliant

