

Heat Shrink Tube,transparent,ID before shrink 0.75'',with UL certificated,48''

length

- **UL certificated**
- **Good weatherproof performance**
- **Various range of application**



Product Classification

Material Code	6007261
Part Number	-
Status	Active
Detail description	Heat shrink tube,transparent,ID before shrink 0.75'',with UL certificated,48''length

General Specifications

Material	Ethylene vinyl acetate copolymer(EVA)
Applied pole size	φ10.4-19.0mm
Color	Transparent
Glued(Y/N)	N

Dimensions

Inner diameter(ID) before shrink	20 mm 0.75 in
Thickness before shrink	0.4 mm 0.016 in
Inner diameter(ID) after shrink	≤10 mm ≤0.39 in
Thickness after shrink	0.83 mm 0.033 in
Shrink ratio	2:1

Environmental Specifications

Operating temperature	-55°C to +125°C (-67°F to +257°F)
Temperature starting shrink	+70°C (158°F)
Temperature totally shrink	+125°C (+257°F)

Packaging and Weights

Bag width	130 mm 5.12 in
Roll height	34 mm 0.11 in

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised:Feb 25, 2023
Public

Bag length	1370 mm 53.94 in
Length per pcs	1.22m 48 in
Packaging quantity and UOM	Bag of 100
Weight gross	0.847 kg 1.87 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UL	Compliant

