

Heat Shrink Tube,transparent,ID before shrink 0.75",with UL certificated

- **UL certificated**
- **Good weatherproof performance**
- **Various range of application**

**Product Classification**

Material Code	6007255
Part Number	-
Status	Active
Detail description	Heat shrink tube,transparent,ID before shrink 0.75",with UL certificated

General Specifications

Material	Ethylene vinyl acetate copolymer(EVA)
Applied pole size	φ10.4-19.0mm
Color	Transparent
Glued(Y/N)	N

Dimensions

Inner diameter(ID) before shrink	20 mm 0.75 in
Thickness before shrink	0.4 mm 0.016 in
Inner diameter(ID) after shrink	≤10 mm ≤0.39 in
Thickness after shrink	0.83 mm 0.033 in
Shrink ratio	2:1

Environmental Specifications

Operating temperature	-55°C to +125°C(-67°F to +257°F)
Temperature starting shrink	+70°C(158°F)
Temperature totally shrink	+125°C(+257°F)

Packaging and Weights

Roll diameter	500 mm 1.64 in
Roll height	34 mm 0.11 in
Meter per roll	30.5m

Packaging quantity and UOM	1 roll
Weight gross	1.17 kg 2.58 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UL	Compliant

