

**Heat Shrink Tube,transparent,ID before shrink 1",with UL certificated**

- **UL certificated**
- **Good weatherproof performance**
- **Various range of application**

**Product Classification**

Material Code	6007256
Part Number	-
Status	Active
Detail description	Heat shrink tube,transparent,ID before shrink 1",with UL certificated

**General Specifications**

Material	Ethylene vinyl acetate copolymer(EVA)
Applied pole size	φ6.2-11.0mm
Color	Transparent
Glued(Y/N)	N

**Dimensions**

Inner diameter(ID) before shrink	26 mm   1.0 in
Thickness before shrink	0.45 mm   0.018 in
Inner diameter(ID) after shrink	≤12.5 mm   ≤0.5 in
Thickness after shrink	0.9 mm   0.036 in
Shrink ratio	2:1

**Environmental Specifications**

Operating temperature	-55°C to +125°C (-67°F to +257°F)
Temperature starting shrink	+70°C (158°F)
Temperature totally shrink	+125°C (+257°F)

**Packaging and Weights**

Roll diameter	500 mm   1.64 in
Roll height	34 mm   0.11 in
Meter per roll	30.5m

Packaging quantity and UOM	1 roll
Weight gross	1.469 kg   3.24 lb

---

**Certifications and Compliance**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UL	Compliant

