

## Hexagonal Insulators, with 5/8" insert

- Robust design & material for outdoor use
- Used for electrical applications
- Operation Temperature -20~140 °C
- RoHS certified



### Product Classification

Material Number	6005721
Part Number	-
Status	Active
Detail Description	Hexagonal Buss Bar Insulators, with 5/8" aluminum insert

### General Specifications

Body Material	DMC
Insert Material	Aluminum
Mounting Screw Depth	20 mm   0.787 in
Mounting Screw Size	5/8"-18UNC

### Dimensions

Height	70 mm   0.787 in
Opposite Side Dimension	63.5 mm   2.5 in

### Environmental Specifications

Operating Temperature	-20 °C to +140 °C
-----------------------	-------------------

### Electrical Specifications

Voltage Withstand	3 KV
Tensile Strength	3500 N   800 Lbs
Thread Torque	30 N.m

### Packaging and Weights

Height, packed	320 mm   12.59 in
Width, packed	220 mm   8.66 in
UOM	Pcs
Packaging	Bag
Weight, gross	0.229 kg   0.504 lb

### Certifications and Compliance

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Apr 6, 2023  
 Public

DATASHEET

**MAXDAO**

ISO 9001:2015

Designed, manufactured and/or distributed under this  
quality management system

RoHS

Compliant

TEMPLATE# ITM-04-01 VERSION A/5 DATE 04/10/2023

**For more information, please visit:**  
[www.maxdao.com](http://www.maxdao.com)



**©Copyright 2023 Maxdao Inc. All rights reserved.**

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Apr 6, 2023

Public

Page 2 of 2