

**High Speed Grounding Kit,for cable 1/2",0.5m**

- Easy and quick installation
- Low contact transition resistance of maximum 20mΩ
- Suitable for screen diameter of cable OD 1/2"
- Operation Temperature -40~70 °C
- Waterproof IP68

**Product Classification**

Material Number	6006489
Status	Active
Detail Description	High Speed Grounding Kit,for cable 1/2",0.5m,installation accessories included

**General Specifications**

Bonding Conductor Jacket Material	PVC
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	6 AWG
Grounding Strap Material	Copper
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel

**Dimensions**

Bonding Conductor Length	0.5m   19.7 in
Lug Hole Size	M8
Screw Size	M8x25

**Electrical Specifications**

Contact Transition Resistance	Maximum 20mΩ
-------------------------------	--------------

**Packaging and Weights**

Height, packed	180 mm   7.0 in
Width, packed	310 mm   12.2 in
Length, packed	400 mm   15.75 in

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 23, 2023

Public

Included	Grounding kit   M8*25 screw   M8 spring washer   M8 flat washer   M8 nut
UOM	1 Kit
Packaging	Bag
Weight, gross	0.182 kg   0.401 lb

---

### Certifications and Compliance

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

