

High Speed Grounding Kit,for cable 1-5/8",0.6m

- Easy and quick installation
- Low contact transition resistance of maximum 20mΩ
- Suitable for screen diameter of cable OD 1-5/8 in
- Operation Temperature -40~70 °C
- Waterproof IP68

**Product Classification**

Material Code	6003510
Status	Active
Detail Description	High Speed Grounding Kit,for cable 1-5/8 in,0.6m, installation accessories including

General Specifications

Bonding Conductor Jacket Material	PVC
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	6 AWG
Grounding Strap Material	Copper
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel

Dimensions

Bonding Conductor Length	0.6m 23.6 in
Lug Hole Size	M8
Screw Size	M8*25

Electrical Specifications

Contact Transition Resistance	Maximum 20mΩ
-------------------------------	--------------

Packaging and Weights

Height, packed	180 mm 7.0 in
Width, packed	310 mm 12.2 in
Length, packed	400 mm 15.75 in

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 27, 2023

Public

Included	Grounding kit M8*25 screw M8 spring washer M8 flat washer M8 nut
Packaging Quantity and UOM	1 Kit
Weight, gross	0.19 kg 0.42 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

