VERSION A/5 DATE 04/10/2023



Hoisting Grip, Pre-Laced, for 0.50-0.62 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- The pre-laced is used when top connector is installed after the antenna transmission line is hoisted.
- Stainless steel wire mesh is for indoor or outdoor use.
- CE certified



Product Classification	
Material Number	6007306
Part Number	-
Status	Active
Detail Description	Hoisting Grip, Pre-Laced, for 0.50-0.62 in Cable
Details	
Cable Range	0.50-0.62 in 12.7-15.7 mm
Mesh Length	11.0 in 279.4 mm
Eye Length	7.0 in 177.8 mm
Approximate Break Strength	1600 lbs 725.7 kg
Working Load	320.0 lbs 145.1 kg (Safety Factor 5*)
Maximum Spacing Intervals	200 ft 60.96 m
Mesh Material	Stainless Steel
Support Clamp	Included
Warning Label	Yellow Mylar
Packaging and Weights	
UOM	1 pcs
Packaging	Bag
Weight, gross	0.15 lb 0.07 kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant

For more information, please visit: www.maxdao.com

