

Hoisting Grip, Pre-Laced, for 0.62-0.74 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- The pre-laced is used when top connector is installed after the antenna transmission line is hoisted.
- Stainless steel wire mesh is for indoor or outdoor use.
- CE certified



Product Classification

Material Number	6007307
Part Number	-
Status	Active
Detail Description	Hoisting Grip, Pre-Laced, for 0.62-0.74 in Cable

Details

Cable Range	0.62-0.74 in 15.7-19.0 mm
Mesh Length	11.0 in 279.4 mm
Eye Length	8.0 in 203.2 mm
Approximate Break Strength	2060 lbs 934.4 kg
Working Load	412.0 lbs 186.9 kg (Safety Factor 5*)
Maximum Spacing Intervals	200 ft 60.96 m
Mesh Material	Stainless Steel
Support Clamp	Included
Warning Label	Yellow Mylar

Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.176 lb 0.081 kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.
 The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
 Revised: May 10, 2023
 Public