

## Hoisting Grip, Pre-Laced, for 1.25-1.49 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- The pre-laced is used when top connector is installed after the antenna transmission line is hoisted.
- Stainless steel wire mesh is for indoor or outdoor use.
- CE certified




---

### Product Classification

Material Number	6005036
Part Number	-
Status	Active
Detail Description	Hoisting Grip, Pre-Laced, for 1.25-1.49 in Cable

---

### Details

Cable Range	1.25-1.49 in   31.8-37.8 mm
Mesh Length	16.0 in   406.4 mm
Eye Length	10.0 in   254.0 mm
Approximate Break Strength	4000 lbs   1814.3 kg
Working Load	800 lbs   362.8 kg (Safety Factor 5*)
Maximum Spacing Intervals	200 ft   60.96 m
Mesh Material	Stainless Steel
Support Clamp	Included
Warning Label	Yellow Mylar

---

### Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.34 lb   0.15 kg

---

### Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.  
 The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.  
 Revised: May 11, 2023  
 Public