Hoisting Grip, Pre-Laced, for 1.38-1.65 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- The pre-laced is used when top connector is installed after the antenna transmission line is hoisted.
- Stainless steel wire mesh is for indoor or outdoor use.

Revised: May 11, 2023

Public

• CE certified

fin

 \bowtie



| Product Classification | |
|---|--|
| Material Number | 6001414 |
| Part Number | - |
| Status | Active |
| Detail Description | Hoisting Grip, Pre-Laced, for 1.38-1.65 in Cable |
| Details | |
| Cable Range | 1.38-1.65 in 35.0-42.0 mm |
| Mesh Length | 24.0 in 609.6 mm |
| Eye Length | 10.0 in 254.0 mm |
| Approximate Break Streng | gth 3300 lbs 1451.5 kg |
| Working Load | 660 lbs 299.4 kg (Safety Factor 5*) |
| Maximum Spacing Interva | als 200 ft 60.96 m |
| Mesh Material | Stainless Steel |
| Support Clamp | Included |
| Warning Label | Yellow Mylar |
| Packaging and Weights | |
| UOM | 1 pcs |
| Packaging | Bag |
| Weight, gross | 0.38 lb 0.17 kg |
| Certifications and Comp | liance |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| CE | Compliant |
| For more information, please visit: www.maxdao.com | ©Copyright 2023 Maxdao Inc. All rights reserved. Page 1 of 1 The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Bevised: May 11 2023 |