

Hoisting Grip, Pre-Laced, for 1.80 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- The pre-laced is used when top connector is installed after the antenna transmission line is hoisted.
- Stainless steel wire mesh is for indoor or outdoor use.
- CE certified



Product Classification

| | |
|--------------------|---|
| Material Number | 6004026 |
| Part Number | - |
| Status | Active |
| Detail Description | Hoisting Grip, Pre-Laced, for 1.80 in Cable |

Details

| | |
|----------------------------|--|
| Cable Range | 1.80 in 45.7 mm |
| Mesh Length | 24.0 in 609.6 mm |
| Eye Length | 10.0 in 254.0 mm |
| Approximate Break Strength | 5600 lbs 2540.1 kg |
| Working Load | 1120 lbs 508.0 kg (Safety Factor 5*) |
| Maximum Spacing Intervals | 200 ft 60.96 m |
| Mesh Material | Stainless Steel |
| Support Clamp | Included |
| Warning Label | Yellow Mylar |

Packaging and Weights

| | |
|---------------|-------------------|
| UOM | 1 pcs |
| Packaging | Bag |
| Weight, gross | 0.51 lb 0.23 kg |

Certifications and Compliance

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| CE | Compliant |

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.
 The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
 Revised: May 11, 2023
 Public