

Jumper cable, 1/2" flexible cable, 4.3-10 male to DIN right male, 2 meter

- Stable premium VSWR, outstanding and consistent intermodulation performance
- Improves network performance, reduces the number of dropped calls and avoids revenue loss
- RoHS certified

**Product Classification**

Material Code	6004057
Part Number	-
Status	Active
Detail Description	Jumper cable, 1/2" flexible cable, 4.3-10 male to 7/16 DIN right male, 2 meter

General Specifications

Connector 1 Type	4.3-10 male
Connector 2 Type	7/16 DIN right male
Cable Type	1/2" Flexible Cable

Dimensions

Length	2 Meter
--------	---------

Electrical Specifications

Characteristic Impedance	50 ohm
Frequency Range	DC-3GHz
VSWR	≤1.15(DC-3GHz)
PIM3	≤-160dBc
Mating Cycles	≥500

Environmental Specifications

Installation Temperature	-25 °C to +60 °C
Operating Temperature	-40 °C to +85 °C
Waterproof	IEC 60529, IP68

Packaging and Weights

Height, packed	300 mm 11.81 in
Width, packed	300 mm 11.81 in
Length, packed	60 mm 2.36 in



Packaging Quantity and UOM	1 Pcs
Weight, gross	0.91 kg 2.01 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

