

Jumper cable, 1/2" superflexible cable, 4.3-10 male to 4.3-10 male, 6 meter

- Stable premium VSWR, outstanding and consistent intermodulation performance
- Improves network performance, reduces the number of dropped calls and avoids revenue loss
- RoHS certified



Product Classification

Material Code	6006752
Part Number	-
Status	Active
Detail Description	Jumper cable, 1/2" superflexible cable, 4.3-10 male to 4.3-10 DIN male, 6 meter

General Specifications

Connector 1 Type	4.3-10 male
Connector 2 Type	4.3-10 male
Cable Type	1/2" Superflexible Cable

Dimensions

Length	6 Meter
--------	---------

Electrical Specifications

Characteristic Impedance	50 ohm
Frequency Range	DC-3GHz
VSWR	≤1.15(DC-3GHz)
PIM3	≤-160dBc
Mating Cycles	≥500

Environmental Specifications

Installation Temperature	-25 °C to +60 °C
Operating Temperature	-40 °C to +85 °C
Waterproof	IEC 60529, IP68

Packaging and Weights

Height, packed	100 mm 3.93 in
Width, packed	500 mm 19.68 in
Length, packed	500 mm 19.68 in

Packaging Quantity and UOM	1 Pcs
Weight, gross	1.91kg 4.21 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

