

Jumper cable, 1/2" superflexible cable, DIN male to DIN male right, 9 meter

- Stable premium VSWR, outstanding and consistent intermodulation performance
- Improves network performance, reduces the number of dropped calls and avoids revenue loss
- RoHS certified

**Product Classification**

Material Code	6003466
Part Number	-
Status	Active
Detail Description	Jumper cable, 1/2" superflexible cable, 7/16 DIN male to 7/16 DIN male right angle, 9 meter

General Specifications

Connector 1 Type	7/16 DIN male
Connector 2 Type	7/16 DIN male right angle
Cable Type	1/2" Superflexible Cable

Dimensions

Length	9 Meter
--------	---------

Electrical Specifications

Characteristic Impedance	50 ohm
Frequency Range	DC-3GHz
VSWR	≤1.15(DC-3GHz)
PIM3	≤-160dBc
Mating Cycles	≥500

Environmental Specifications

Installation Temperature	-25 °C to +60 °C
Operating Temperature	-40 °C to +85 °C
Waterproof	IEC 60529, IP68

Packaging and Weights

Height, packed	300 mm 11.81 in
Width, packed	300 mm 11.81 in
Length, packed	60 mm 2.36 in
Packaging Quantity and UOM	1 Pcs

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 25, 2023

Public

Weight, gross

0.8 kg | 1.76 lb

Certifications and Compliance

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

ROHS

Compliant

