

**Liquidtight Conduit Connector, Malleable Iron, NPT 1", Straight Male, Insulated**


- Be Used When Liquidtight Conduit is in Tough, Industrial and Corrosive Applications
- Liquidtight, Raintight, Oiltight for Protection and Long Life in Wet, Dusty and Corrosive Environments
- Hex Shaped Gland Nut Allows for Easy Wrenching, Providing a Fast, Tight Installation
- Reusable, Long Ferrule Prevents Pull-Out and Tight Bend Conduit Pop-Out
- Furnished with Locknut and Sealing Ring
- UL&CSA, CE certified

**Classification**

Material Number	6007073
Part Number	-
Status	Active
Detail Description	Liquidtight conduit connector, malleable iron, NPT 1", straight male, insulated

**General Specifications**

Trade Size	NPT1"
Body Material	Zinc Plated Malleable Iron
Compression Nut Material	Zinc plated steel
Non-metallic Material	Nylon

**Dimensions**

Dimension A	1.13 in   28.7 mm
Dimension B	0.63 in   16.0 mm
Dimension C	1.76 in   44.8 mm

**Performance**

Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
---------------------	--

**Package**

UOM	1 pcs
Packaging	Carton
Weight, gross	0.319 lb   0.145 kg

**Certifications**

For more information, please visit:  
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 31, 2023

Public

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

UL&CSA

Compliant

CE

Compliant

