

Liquidtight Conduit Connector, Malleable Iron, NPT 3/4", 45 Degree Male, Insulated

- Be Used When Liquidtight Conduit is in Tough, Industrial and Corrosive Applications
- Liquidtight, Raintight, Oiltight for Protection and Long Life in Wet, Dusty and Corrosive Environments
- Hex Shaped Gland Nut Allows for Easy Wrenching, Providing a Fast, Tight Installation
- Reusable, Long Ferrule Prevents Pull-Out and Tight Bend Conduit Pop-Out
- Furnished with Locknut and Sealing Ring
- UL&CSA, CE certified




Classification

| | |
|--------------------|--|
| Material Number | 6007078 |
| Part Number | - |
| Status | Active |
| Detail Description | Liquidtight conduit connector, malleable iron, NPT 3/4", 45 degree male, insulated |

General Specifications

| | |
|--------------------------|----------------------------|
| Trade Size | NPT3/4" |
| Body Material | Zinc Plated Malleable Iron |
| Compression Nut Material | Zinc plated steel |
| Non-metallic Material | Nylon |

Dimensions



| | |
|-------------|-------------------|
| Dimension A | 2.10 in 53.3 mm |
| Dimension B | 0.65 in 16.5 mm |
| Dimension C | 1.46 in 37.1 mm |

Performance

| | |
|---------------------|--|
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
|---------------------|--|

Package

| | |
|---------------|---------------------|
| UOM | 1 pcs |
| Packaging | Carton |
| Weight, gross | 0.298 lb 0.135 kg |



Certifications

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| UL&CSA | Compliant |
| CE | Compliant |

