

Liquidtight Conduit Connector, Malleable Iron, NPT 3/4", 90 Degree Male, Insulated

- Be Used When Liquidtight Conduit is in Tough, Industrial and Corrosive Applications
- Liquidtight, Raintight, Oiltight for Protection and Long Life in Wet, Dusty and Corrosive Environments
- Hex Shaped Gland Nut Allows for Easy Wrenching, Providing a Fast, Tight Installation
- Reusable, Long Ferrule Prevents Pull-Out and Tight Bend Conduit Pop-Out
- Furnished with Locknut and Sealing Ring
- UL&CSA, CE certified




Classification

Material Number	6007076
Part Number	-
Status	Active
Detail Description	Liquidtight conduit connector, malleable iron, NPT 3/4", 90 degree male, insulated

General Specifications

Trade Size	NPT3/4"
Body Material	Zinc Plated Malleable Iron
Compression Nut Material	Zinc plated steel
Non-metallic Material	Nylon

Dimensions



Dimension A	1.60 in 40.6 mm
Dimension B	0.65 in 16.5 mm
Dimension C	1.46 in 37.1 mm

Performance

Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
---------------------	--

Package

UOM	1 pcs
Packaging	Carton
Weight, gross	0.364 lb 0.165 kg



Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant
CE	Compliant

