

Liquidtight Conduit Connector, Malleable Iron, NPT 1", 45 Degree Male, Insulated


- Be Used When Liquidtight Conduit is in Tough, Industrial and Corrosive Applications
- Liquidtight, Raintight, Oiltight for Protection and Long Life in Wet, Dusty and Corrosive Environments
- Hex Shaped Gland Nut Allows for Easy Wrenching, Providing a Fast, Tight Installation
- Reusable, Long Ferrule Prevents Pull-Out and Tight Bend Conduit Pop-Out
- Furnished with Locknut and Sealing Ring
- UL&CSA, CE certified

**Classification**

Material Number	6007079
Part Number	-
Status	Active
Detail Description	Liquidtight conduit connector, malleable iron, NPT 1", 45 degree male, insulated

General Specifications

Trade Size	NPT1"
Body Material	Zinc Plated Malleable Iron
Compression Nut Material	Zinc plated steel
Non-metallic Material	Nylon

Dimensions

Dimension A	2.50 in 63.5 mm
Dimension B	0.70 in 17.8 mm
Dimension C	1.76 in 44.7 mm

Performance

Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
---------------------	--

Package

UOM	1 pcs
Packaging	Carton
Weight, gross	0.493 lb 0.223 kg

Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant
CE	Compliant

