

P clamp,for φ10mm cable

- Manufactured by EPDM & stainless steel
- Excellent for outdoor & indoor use
- Easy to install



| Material Code | 6006905 |
|-------------------------------|--|
| Part Number | - |
| Status | Active |
| Detail description | Forφ10mm cable,mounting holeφ6.5mm |
| General Specifications | |
| Material | EPDM rubber & SUS304 band |
| Cable type | Corrugated Elliptical Waveguide Smoothwall |
| Cable size | Ф10mm |
| Color | Black rubber and natural color of SUS304 |
| Dimensions | |
| Inner hole diameter for cable | 10 mm 0.39 in |
| Mounting hole | 6.5 mm 0.26 in |
| Nominal size | Ф10 mm 0.39 in |
| Band width | 15 mm 0.59 in |
| Environmental Specifications | |
| Operating temperature | -50-+150 ℃ |
| UV resistance | ≥1000Hours,based on ISO 4892-3 |
| Packaging and Weights | |
| Bag,width | 180 mm 7.09 in |
| Bag,length | 270 mm 10.63 in |
| Included | SUS304 band and rubber cushion |
| Packaging quantity and UOM | Bag of 100 |
| Weight, gross | 0.74 kg 1.63 lb |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this |
| | quality management system |
| ROHS | Compliant |

www.maxdao.com

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised:Feb 20, 2023 Public

