

**Power cable, 16AWG/2C blue&grey UL2464, 100 meter**

- **Annealed Stranded Tin Copper Conductor**
- **100% Aluminum Foil Coverage**
- **UL, RoHS certified**

**Product Classification**

Material Code	6003743
Part Number	-
Status	Active
Detail Description	Power cable, 16AWG/2 conductors UL2464, black PVC jacket, blue&grey conductor, 100 meter

**General Specifications**

Conductor Gauge	16AWG
Conductor Material	Stranded tinned copper
Conductor Number	2
Insulation Material	PVC
Insulation Color	Blue & Grey
Overall Shielding Type	Aluminum foil
Drain Wire Material	Tinned copper
Shielding Material	Tinned copper
Shielding Type	Braid
Jacket Material	PVC
Jacket Color	Black

**Dimensions**

Conductor Structure	26/0.254±0.008TS
Insulation Diameter	2.4 mm   0.09 in
Jacket Diameter	7.5 mm   0.29 in
Length	100 Meter

**Electrical Specifications**

Voltage	300V
---------	------

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 25, 2023

Public

Flame Retardant	VW-1
-----------------	------

---

**Environmental Specifications**


---

Operating Temperature	-20 °C to +80 °C
-----------------------	------------------

---

**Packaging and Weights**


---

Height, packed	100 mm   3.94 in
----------------	------------------

Width, packed	300 mm   11.81 in
---------------	-------------------

Length, packed	300 mm   11.81 in
----------------	-------------------

Packaging Quantity and UOM	1 Pcs
----------------------------	-------

Weight, gross	10.5 kg   23.14 lb
---------------	--------------------

---

**Certifications and Compliance**


---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

ROHS	Compliant
------	-----------

UL	Compliant
----	-----------