

Power cable, 16AWG/2C blue&grey UL2464, 50 meter

- **Annealed Stranded Tin Copper Conductor**
- **100% Aluminum Foil Coverage**
- **UL, RoHS certified**

**Product Classification**

Material Code	6003742
Part Number	-
Status	Active
Detail Description	Power cable, 16AWG/2 conductors UL2464, black PVC jacket, blue&grey conductor, 50 meter

General Specifications

Conductor Gauge	16AWG
Conductor Material	Stranded tinned copper
Conductor Number	2
Insulation Material	PVC
Insulation Color	Blue & Grey
Overall Shielding Type	Aluminum foil
Drain Wire Material	Tinned copper
Shielding Material	Tinned copper
Shielding Type	Braid
Jacket Material	PVC
Jacket Color	Black

Dimensions

Conductor Structure	26/0.254±0.008TS
Insulation Diameter	2.4 mm 0.09 in
Jacket Diameter	7.5 mm 0.29 in
Length	50 Meter

Electrical Specifications

Voltage	300V
---------	------

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 25, 2023

Public

Flame Retardant VW-1

Environmental Specifications

Operating Temperature -20 °C to +80 °C

Packaging and Weights

Height, packed 80 mm | 3.15 in

Width, packed 300 mm | 11.81 in

Length, packed 300 mm | 11.81 in

Packaging Quantity and UOM 1 Pcs

Weight, gross 5.9 kg | 13 lb

Certifications and Compliance

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

ROHS Compliant

UL Compliant

