

## Quick Install round member adapter, stainless steel passivation, for 150-250mm round member

- Wider operating range
- for attaching to round members
- Used indoor or outdoor



### Product Classification

Material Number	6004365
Part Number	-
Status	Active
Detail Description	Quick Install round member adapter, stainless steel 304 passivation, for 150-250mm round member

### General Specifications

Material	Stainless steel 304
Surface Treatment	Passivation and sealing

### Dimensions

Band Width	14 mm   0.551 in
Band Thickness	0.6 mm   0.024 in
Screw Type	Slotted Hex Head
Hex Head Size	7.9 mm   5/16 in
Size Range	150-250 mm

### Mechanical Specifications

Installation Torque	4.0-5.1 N.m   35-45 in.lbs
Minimum Destructive Torque	6.8 N.m   60 in.lbs

### Environmental Specifications

Salt Spray	ASTM B117, 720 hours
------------	----------------------

### Packaging and Weights

Bag Width, packed	310 mm   12.20 in
Bag Length, packed	250 mm   9.84 in
Packaging Quantity and UOM	1 Pcs
Weight, gross	0.17 kg   0.37 lb

### Certifications and Compliance

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 18, 2023

Public

DATASHEET

**MAXDAO**

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

TEMPLATE# ITM-04-01 VERSION A/3 DATE 03/04/2023

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 18, 2023

Public