

Quick Install round member adapter, stainless steel passivation, for 25-125mm round member

- Wider operating range
- for attaching to round members
- Used indoor or outdoor



Product Classification

Material Number	6005139
Part Number	-
Status	Active
Detail Description	Quick Install round member adapter, stainless steel 304 passivation, for 25-125mm round member

General Specifications

Material	Stainless steel 304
Surface Treatment	Passivation and sealing

Dimensions

Band Width	12.6 mm 0.496 in
Band Thickness	0.6 mm 0.024 in
Screw Type	Slotted Hex Head
Hex Head Size	7.9 mm 5/16 in
Size Range	25-125 mm

Mechanical Specifications

Installation Torque	4.0-5.1 N.m 35-45 in.lbs
Minimum Destructive Torque	6.8 N.m 60 in.lbs

Environmental Specifications

Salt Spray	ASTM B117, 720 hours
------------	----------------------

Packaging and Weights

Bag Width, packed	310 mm 12.20 in
Bag Length, packed	250 mm 9.84 in
Packaging Quantity and UOM	1 Pcs
Weight, gross	0.048 kg 0.105 lb

Certifications and Compliance

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 17, 2023

Public

DATASHEET

MAXDAO

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

TEMPLATE# ITM-04-01 VERSION A/3 DATE 03/04/2023

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 17, 2023

Public

Page 2 of 2