

RF adapter, N male to N male

- Excellent low PIM performance
- RoHS certified



Product Classification

Material Code	6006567
Part Number	-
Status	Active
Detail Description	RF adapter, N male to N male

General Specifications

Body Material	Brass
Body Surface Treatment	Copper-Tin-Zinc plating
Insulator Material	PTFE
Conductor PIN Material	Phosphor bronze
Conductor PIN Surface Treatment	Ag plating
Connector 1 Type	N female
Connector 2 Type	N female

Dimensions

Length	35 mm
--------	-------

Electrical Specifications

Characteristic Impedance	50 ohm
Frequency Range	DC-11GHz
VSWR	≤ 1.10 (3000MHZ)
PIM	≤ -155 dBc
Dielectric Withstanding Voltage	≥ 2500 V RMS, 50Hz, at sea level
Contact Resistance	Inner contact ≤ 1.0 m Ω Outer contact ≤ 0.4 m Ω
Dielectric Resistance	≥ 5000 M Ω
Durability	Mating cycles ≥ 500 cycles

Environmental Specifications

Operating Temperature -40 °C to +85 °C

Packaging and Weights

Height, packed 70 mm | 2.75 in

Width, packed 40 mm | 1.57 in

Length, packed 40 mm | 1.57 in

Packaging Quantity and UOM 1 Pcs

Weight, gross 0.05 kg | 0.11 lb

Certifications and Compliance

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

RoHS Compliant

