MAXDAO

Radiating Clamp Kit with fireproof ring, for 1/2 in cable

- Easy and quick installation
- Robust design & material for outdoor / indoor use
- Fixed wall distance 80 mm
- Operation Temperature -40~85 °C



Product Classification	
-	
Active	
Radiating Clamp kit with fireproof ring for 1/2 in radiating cable	
Clamp & 80mm base & ST4.8*125 screw & M6*30 wall plug & fireproof ring	
1	
Black	
Polyamide PA6 Low Smoke Zero Halogen	
Polyamide PA6 Low Smoke Zero Halogen	
Stainless steel	
Polyamide PA6	
Stainless steel	
1/2 in	
10.0 m 32.8 ft	
UL94V-0	
180 mm 7.0 in	
310 mm 12.2 in	

For more information, please visit: www.maxdao.com ©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 21, 2023 Public



Page 1 of 2

MAXDAO

DATASHEET

Length, packed	400mm 15.75 in
Packaging Quantity and UOM	1 Kit
Weight, gross	0.11 kg 0.25 lb
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

For more information, please visit: www.maxdao.com

 \square in

©Copyright 2023 Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 21, 2023 Public

Page 2 of 2