

Stackable Snap-in Hanger, For 1/2" Cable

- Easy and quick installation, no hardware needed
- Robust design & material for outdoor / indoor use
- Install in 3/4 in holes
- Stack up to three cables



Product Classification

| | |
|--------------------|---|
| Item Number | 6001983 |
| Part Number | - |
| Status | Active |
| Detail Description | Stackable snap-in hanger for 1/2 in cable |

General Specifications

| | |
|---------------|------------------------------|
| Material Type | Stainless steel 304 |
| Color | Silver |
| Cable Type | Braided coaxial hybrid cable |
| Mounting | 3/4 in drilled cable ladder |

Dimensions

| | |
|-------------------------------|--------------------|
| Height | 1.594 in 40.5 mm |
| Width | 0.905 in 23.0 mm |
| Length | 3.602 in 59.0 mm |
| Compatible Jacket OD, maximum | 0.67 in 17.0 mm |
| Compatible Diameter, minimum | 0.59 in 15.0 mm |
| Nominal Size | 1/2 in |
| Max Stack | 3 |

Environmental Specifications

| | |
|-------------------------|---|
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| UV Resistance | ≥720 hours, base on ISO4892.3-1994 |
| Corrosion Resistance | ≥168 hours in salt spray chamber, base on IEC 60068 -2-11 |
| Vibration Survival Test | ≥6 hours at resonant frequency, base on IEC 60068 -2-6 |

Packaging and Weights

| | |
|----------------|-------------------|
| Height, packed | 1.77 in 45 mm |
| Width, packed | 7.874 in 200 mm |

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Apr 9, 2024
 Public

| | |
|--------------------------------------|--|
| Length, packed | 7.874 in 200 mm |
| Included | Stackable snap-in hanger, Installation sheet |
| Packaging Quantity and UOM | Kit of 10 |
| Weight, gross | 0.35 lb 0.16 kg |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

