

Stackable Snap-in Hanger, for 7/8 in cable

- Easy and quick installation, no hardware needed
- Robust design & material for outdoor / indoor use
- Install in 3/4 in holes
- Stack up to three cables



Product Classification

| | |
|--------------------|---|
| Material Code | 6003199 |
| Part Number | - |
| Status | Active |
| Detail Description | Stackable snap-in hanger for 7/8 in cable |

General Specifications

| | |
|---------------|------------------------------|
| Material Type | Stainless steel 304 |
| Color | Silver |
| Cable Type | Braided coaxial hybrid cable |
| Mounting | 3/4 in drilled cable ladder |

Dimensions

| | |
|-------------------------------|--------------------|
| Height | 1.575 in 40 mm |
| Width | 1.71 in 43.5 mm |
| Length | 2.48 in 63 mm |
| Compatible Jacket OD, maximum | 1.22 in 31 mm |
| Compatible Diameter, minimum | 1.051 in 26.7 mm |
| Nominal Size | 7/8 in |

Environmental Specifications

| | |
|-------------------------|---|
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| UV Resistance | ≥720 hours, base on ISO4892.3-1994 |
| Corrosion Resistance | ≥168 hours in salt spray chamber, base on IEC 60068 -2-11 |
| Vibration Survival Test | ≥6 hours at resonant frequency, base on IEC 60068 -2-6 |

Packaging and Weights

| | |
|----------------------------|--|
| Height, packed | 1.77 in 45 mm |
| Width, packed | 7.874 in 200 mm |
| Length, packed | 7.874 in 200 mm |
| Included | Stackable snap-in hanger, Installation sheet |
| Packaging Quantity and UOM | kit of 10 |
| Weight, gross | 0.75 lb 0.34 kg |

Certifications and Compliance

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| ROHS | Compliant |

