

Standard Grounding Kit, for 1/4 in and 3/8 in cable, 1.5m

- Easy and quick installation
- Low contact transition resistance of maximum 5mΩ
- Operation Temperature -40~70 °C
- Waterproof IP68

**Product Classification**

Material Code	6006501
Status	Active
Detail Description	Standard grounding kit, for 1/4 in and 3/8 in cable, 1.5m

General Specifications

Bonding Conductor Jacket Material	PVC
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	6 AWG
Grounding Strap Material	Copper
Lug Type	Two-hole lug
Screw Material	Stainless Steel 304
Flat washer Material	Stainless Steel 304
Lock washer Material	Stainless Steel 304
Nut Material	Stainless Steel 304
PVC tape Material	PVC, UL listed
Butyl Rubber Tape Material	Butyl

Dimensions

Bonding Conductor Length	1.5m 60 in
Lug Hole Size	3/8 in, 1/4 in
Screw Size	3/8 x 1 in, 1/4 x 3/4 in
PVC tape Size	0.19mm x 48mm x 6m
Butyl Rubber Tape Size	1.5mm x 60mm x 600mm

Electrical Specifications

Contact Transition Resistance	Maximum 5 mΩ
-------------------------------	--------------

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 09, 2023

Public

Packaging and Weights

Height, packed	180 mm 7.0 in
Width, packed	310 mm 12.2 in
Length, packed	400 mm 15.75 in
Included	Grounding Kit, Hardware Installation Kit
Packaging Quantity and UOM	1 Kit
Weight, gross	0.54 kg 1.19 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

